

VoiceAmp® SpeakEasy™ Portable 5.25" 30 Watt PA Amplifier

Robust sound delivered from a lightweight, durable PA system. The VoiceAmp® SpeakEasy™ is a small, easy to use, portable public address system that delivers loud, clear, and natural sound for small to medium sized audiences. The powerful, class D 30-watt amplifier and 5.25 inch speaker are encased in a durable, lightweight, handcrafted ½ inch-thick birch housing that delivers superb audio quality and is engineered to withstand the most rugged applications. Standard features include a built-in siren, a USB/MP3 player with dedicated volume control, tone control, an auxiliary line input with dedicated volume control and a line output to provide line-level audio to a secondary powered speaker or other audio devices. Power is supplied by either an AC adapter/charger or a built-in rechargeable 14.8V/3A lithium battery pack which provides 10+ hours of continuous operation and can be fully recharged in 4 to 5 hours.

Optional 900MHz wireless switching diversity receiver modules allow the SpeakEasy™ to receive and amplify up to two wireless transmitters used by presenters.



ARG-VA30S VoiceAmp® SpeakEasy™ Technical Specifications

Rated Power Output	30 Watts CLASS D
Max SPL @ Rated Power	90dB @ 1 meter
Frequency Response	60 Hz – 18 kHz
Switch Power Supply/Battery Charger	INPUT 100Vac-240Vac, 50/60Hz 1.5A-0.9A OUTPUT: 18V – 3A
Built-In Battery	14.8V 3000mAh Lithium Polymer Battery Pack
Dimensions	7-5/8" (W) x 7-1/2" (H) x 6-3/8" (D)
Weight	6 lbs
Inputs/Outputs	
Line-IN	Mono 3.5mm jack accepts audio devices that have a line-level output including MP3 players, IPODS and CD players
Mic-IN	Mono ¼" jack accepts wired low impedance dynamic microphones
USB Player	Supports MPEG audio 1, 2 and 2.5; supports layer 1, 2, and 3
Line-OUT	Mono 3.5mm jack provides line-level audio to secondary powered speaker or audio devices having a line-In Input jack.

Optional Wireless Systems - ARG-TX900BP 900MHz Transmitter

Frequency Range	902 MHz – 928 MHz
Frequency Response	20 Hz – 15 kHz
Output Power	10dBm
Mute	Auto when signal lost
Frequency Space	2MHz
S/N Ratio	80dB
Channel Number	CH01 – CH12
Audio Sampling	32KHz
Modulation	QPSK
Audio Input	Mic-IN/Line-IN (ARG-TX900BP)
Charge Power	5V (ARG-TX900BP)
Battery	1200mAh lithium battery pack

NOTE: SPECIFICATIONS SUBJECT TO CHANGE WITHOUT NOTICE!